




Canopy emergency jettisoning:
Push to the left the red flat
knob above the instrument
panel.



Ventilation

Prior to take off check the
proper engagement of the
canopy locks! forward=locked

**This placard must be fitted
in the front and rear
cockpit in full view of the
pilot.**

XIV APPENDIX

XIV.1 Equipment List

Issue May 1980

Minimum equipment

1. Airspeed indicator
 - a. Winter GW 6005 50 - 350 km/h
 - b. PZL PS 08 50 - 350 km/h

2. Altimeter
 - a. Winter 4 HM 6
 - b. Winter 4 FGH 10
 - c. PZL W-12 S

3. Safety harness
 - Gadringer Bagu V-B/1
 - Schugu II-C/V
 - Bogu I-B/V front
 - Bogu I-A/V rear

Additional minimum equipment for aerobatics :

G-meter BM 770 L

Additional minimum equipment for cloud flying :

Turn & bank indicator Apparatebau Gauting WZ-402/31.

- Compass :
- Ludolph FK 5
 - Ludolph FK 16
 - PZL BS-1
 - PZL B-13/KJ

VHF-transceiver

- a. Dittel FSG 15/25
- b. Dittel FSG 16/25
- c. Dittel FSG 40 S
- d. Becker AR 2008/25
- e. Becker AR 2009/25
- f. Avionic Dittel ATR 720