

SHEET:  
1 of 1

ASW 15  
Technical Note  
No. 23-2  
(only applicable to USA)

Alexander Schleicher  
GmbH & Co.  
Segelflugzeugbau  
D-6416 Poppenhausen

General: This Technical Note supplements TN no.23 dated April 21, 1988, LBA-approved April 26, 1988, and TN no.23-1, dated October 18, 1988 and LBA-approved November 17, 1988, and is applicable only to gliders registered in the U.S..

Subject: U.S. product equivalent to AIDOL 100 (to be used for the interior preservation of the wing spar).

Action: The following point is entered in addition :

2.2a: Applicable to the USA only :-

For U.S. registered ASW 15 or ASW 15 B gliders the use of the product DAP Woodlife Clear Wood Preservative is accepted as equivalent to the above AIDOL 100.

When using this DAP product, you will need two treatments of each 100 g. One application of 100 g has to be made as a first step and then the wing must dry off. Afterwards the wing must be rotated by 180° and another 100 g have to be applied. Make sure that DAP Woodlife Clear Wood Preservative has really completely dried out before the glider is taken back into operation.

Notes:

2. Addresses of the institutes:

Please note that only the two following institutes accepted to do the bore core examination :-

Bundesamt für Materialforschung und Prüfung  
Biologische Materialprüfung  
Unter den Eichen 87  
D-1000 Berlin 45  
Tel.: 030-8104-5100

Fraunhofer-Institut für Holzforschung  
Bienroder Weg 54 E  
D-3300 Braunschweig  
Tel.: 0531-3909-336

Poppenhausen, February 8, 1989

ALEXANDER SCHLEICHER  
GmbH & Co.

*Gerhard Waibel*  
(Gerhard Waibel)

This Technical Note has been approved by the LBA under the date of  
(signature: ).

Zwischenhandlungen verpflichten zu Schadenersatz. Alle Rechte für den Fall der Patentierung oder Gebrauchsmuster-Eintragung vorbehalten.

Weitergabe sowie Vervielfältigung dieser Unterlage, Verwertung und Mitteilung ihres Inhalts nicht gestattet, soweit nicht ausdrücklich zugestanden.